



SILL LEVELING BRACKET

SILL-HATCH SIDE ELEVATION
KEY TO VIEW SECTION

NOTE:
STRUTS MUST BE INSTALLED AS SHOWN
W/ CARRIAGE BOLT HEADS IN VERTICAL
SLOT AT BTM END OF STRUT ON DOOR SIDE.
TOP OF STRUTS HAVE HORIZONTAL SLOTS
FOR BOLTS.

SECTION C
OPPOSITE W/O PTS 18 THRU 22

SECTION D

VIEW A
OPPOSITE

HATCH SIDE
HALL SIDE
TINNERMAN DETAILS

NOTE:
10 REQ'D;
MUST BE INSTALLED ON
HALL SIDE OF HEADER
BEFORE ATTACHING
STRUTS W/ BOLTS

INCH DIMENSIONS TOLERANCE UNLESS SHOWN	
SOURCE/SPEC#/FINISH/WT	
THIS INFORMATION IS CONFIDENTIAL AND REMAINS THE PROPERTY OF ELEVATOR SOLUTIONS INTERNATIONAL INC. ITS USE, REPRODUCTION, OR DISSEMINATION WITHOUT THE EXPRESS PERMISSION OF ELEVATOR SOLUTIONS INTERNATIONAL INC. IS STRICTLY PROHIBITED.	
PLOT SCALE: = 9.00	
0 11/20/04	LJP
DATE	CH'K
DESCR	DESCR
DRAWN BY DATE	
LJP 11/20/04	
ELEVATOR SOLUTIONS INTERNATIONAL INC. ARKANSAS CITY, KANSAS	
NAME	
INSTALLATION DETAILS	
2-SPEED RH	
ES-1 ENTRANCE	
ESIB070RB R0, 07-04	
DT24014B03722011	